



Don't paint it... Globalcote it!
www.globalcote.com.au

PREPCOTE SURFACE TREATMENT

Data Sheet

DESCRIPTION

Prepcote Surface Treatment is a preventative treatment to inhibit the growth of moss, lichen or fungi - organic material that occurs on various substrates and surfaces.

FEATURES + BENEFITS

- Water Based** Easy application and easy clean up.
- Forms Barrier** Inhibits growth of moss, lichen or fungi.
- Fast Dry** Recoat after 2 hours.

USES

Apply to sound or weathered substrates prior to the application of the Primecote Sealer Primer.

PERFORMANCE GUIDE

Weather	N/A	Solvent	N/A	Salt	N/A	Abrasion	N/A
Heat	N/A	Acid	N/A	Water	N/A	Alkali	N/A

TYPICAL PROPERTIES

Gloss Level	N/A	Spread Rate	6.0 sqm/L
Gloss Level Ind	N/A	Components	1
Volume Solids (%)	N/A	Shelf life	24 months maximum
Colour	Clear	Wet film per coat	Recommended 0 um
Number of Coats	1 - 2	Touch Dry	Recommended 0 um
V.O.C	Level < 30 g/L	Dry film per coat	30 minutes
Clean Up	Water	Recoat	2 hrs
Thinner	Not Recommended	Size	20 litres

APPLICATION PROCESS

Spray to noses of tiles and any fungi/mould affected areas with an atomising gun. Allow 2 hours prior to coating with the Primecote Sealer Primer. Please note that Prepcote Surface Treatment is not a cleaning product, it is to remain on the surface to form part of the Globalcote system. Prepcote Surface Treatment may also be used as an anti-fungal preparation treatment to other external surfaces prior to painting.

HEALTH + SAFETY

MSDS: Available on request. Please visit the Globalcote Website - www.globalcote.com.au.

RECOMMENDATIONS + PRECAUTIONS

- Always use and store this product in a well ventilated area.
- Always ensure that the surface is sound, clean and dry.
- Wear appropriate safety clothing, shoes, glasses and gloves at all times.
- In the case of emergency please call 000.
- Do not apply where rain is imminent. High humidity may effect curing times. Weather conditions must be considered and deemed suitable before proceeding with application of the Globalcote system.
- Always ensure that the application of the Prepcote Surface Treatment is in accordance with Globalcote recommendations.
- Due care and consideration should be taken where water collection methods are present. Globalcote recommend allowing our system 7 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.
- Always ensure that workplace health and safety methods are used when working with this product at heights.
- Dangerous Goods Class = Not Applicable - Not considered dangerous for transportation of this product.

DISCLAIMER The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use on the Globalcote product are beyond Globalcote's control. Globalcote recommends that the applicator of this product determines the suitability of the Globalcote material and its recommendations prior to use or application.