



The finishing coat.

www.globalcote.com.au

GLOBALCOTE SURFACE TREATMENT DATA SHEET

DESCRIPTION

Globalcote Surface Treatment is a remedial treatment for the removal of moss and fungi, an organic growth which occurs on various substrates and surfaces.

FEATURES + BENEFITS

Water Based	Easy application and easy clean up.
Kills Mould	Prevents re-occurrence of mould/moss lichen growth
Fast Dry	Recoat after 2 hours

USES

Apply to sound or weathered substrates prior to the application of the Globalcote Sealer.

PERFORMANCE GUIDE

Weather	N/A	Solvent	N/A	Salt	N/A	Abrasion	N/A
Heat	N/A	Acid	N/A	Water	N/A	Alkali	N/A

TYPICAL PROPERTIES

Gloss Level	N/A	Spread Rate	6.0 sqm/L
Gloss Level Ind	N/A	Components	1
Volume Solids (%)	20.0	Shelf life	24 months maximum
Colour	Clear	Wet film per coat	Recommended 0 μ m
Number of Coats	1 - 2	Touch Dry	Recommended 0 μ m
Clean Up	Water	Dry film per coat	30 minutes
Thinner	Not Recommended	Recoat	2 hrs
		Size	20 litres

APPLICATION PROCESS

Spray to noses of tiles and any fungi/mould affected areas with an atomising gun. Allow 2 hours to coating with the Globalcote Sealer Primer. Please note that Globalcote Surface Treatment is not a cleaning product, it is to remain on the surface to form part of the Globalcote system. Globalcote Surface Treatment may also be used as an anti-fungal preparation treatment to other external surfaces prior to painting.

HEALTH + SAFETY

MSDS: Available on request. Please visit the Globalcote Website - www.globalcote.com.au

RECOMMENDATIONS + PRECAUTIONS

- Store this product and use in well ventilated spaces
- Always ensure that the surface is sound, clean and dry
- Wear appropriate safety clothing, shoes, glasses and gloves at all times
- In the case of emergency please call 000
- Do not apply where rain is imminent. High humidity may effect curing times. Weather conditions must be considered and deemed suitable before proceeding with application of the Globalcote system
- Always ensure that the application of the Globalcote Surface Treatment is in accordance to the Globalcote recommendations
- Always ensure that prior to application of the Globalcote Surface Treatment - storm water pipes are disconnected - allow 7 days for reconnection
- Always ensure that workplace health and safety methods are used when working with this product at heights.
- Dangerous Goods Class = Not Applicable - Not considered dangerous for transportation of this product

DISCLAIMER The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use on the Globalcote product are beyond Globalcote's control. Globalcote recommends that the applicator of this product determines the suitability of the Globalcote material and its recommendations prior to use or application.