

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** FLEXISTIK

**Recommended Use:** Polyurethane adhesive.

**Supplier:** Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd  
**ABN:** 67 000 049 427  
**Street Address:** 1 Gow Street,  
Padstow, NSW 2211  
Australia  
**Telephone Number:** +61 2 9781 8777  
**Facsimile:** +61 2 9781 8825  
**Emergency Telephone:** **1 800 033 111 (ALL HOURS)**

## 2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

**Risk Phrases:** May cause sensitisation by inhalation.

**Safety Phrases:** Do not breathe vapour. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection.

**Poisons Schedule:** None allocated.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Distillates, petroleum, hydrotreated light	64742-47-8	<3%	R65
Xylene	1330-20-7	<2.5%	R10 R20/21 R38
Diphenylmethane-4,4-diisocyanate MDI	101-68-8	<1%	R20 R36/37/38 R40 R42/43 R48/20
Ingredients determined not to be hazardous	-	to 100%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

# Safety Data Sheet

**Skin Contact:**

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. A component of this material can be absorbed through the skin with resultant toxic effects. Seek immediate medical assistance.

**Eye Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:**

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

**Medical attention and special treatment:**

Treat symptomatically. Effects may be delayed.

## 5. FIRE FIGHTING MEASURES

**Hazards from combustion products:**

Combustible paste. On burning will emit toxic fumes, including those of hydrogen cyanide, isocyanate vapours, oxides of carbon and oxides of nitrogen.

**Precautions for fire fighters and special protective equipment:**

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

**Suitable Extinguishing Media:**

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency procedures:**

If contamination of sewers or waterways has occurred advise local emergency services.

**Methods and materials for containment and clean up:**

SMALL SPILLS: Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS: Wear protective equipment to prevent skin and eye contact and breathing in vapours. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

## 7. HANDLING AND STORAGE

**Conditions for safe storage:**

Store in cool place and out of direct sunlight. Keep dry - reacts with water, may lead to drum rupture. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

**Precautions for safe handling:**

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour, mists and aerosols.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Product Name: FLEXISTIK  
Substance No: 000000022733

Issued: 26/09/2011  
Version: 2

# Safety Data Sheet



Isocyanates, all (as -NCO): 8hr TWA = 0.02 mg/m<sup>3</sup>, 15 min STEL = 0.07 mg/m<sup>3</sup>, Sen  
Xylene (o-, m-, p- isomers): 8hr TWA = 350 mg/m<sup>3</sup> (80 ppm), 15 min STEL = 655 mg/m<sup>3</sup> (150 ppm)

As published by the National Occupational Health and Safety Commission.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

'Sen' Notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## Engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use.

## Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Blue



MANUFACTURE, PACKAGING AND TRANSPORT: Blue - Wear overalls (or 'issued' long pants and long sleeve tops), safety boots, gloves and face shield or chemical goggles. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If inhalation risk exists due to processing vapours, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

FOR CONSUMER USE: When using the product as a sealant: wear protective clothing, impervious gloves and safety glasses. Use with adequate ventilation.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Paste  
**Colour:** White / Black / Grey  
**Odour:** Light  
**Odour Threshold:** Not available

Product Name: FLEXISTIK  
Substance No: 000000022733

Issued: 26/09/2011  
Version: 2

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Solubility:</b>	Insoluble in water. Reacts with water. Uncured material is soluble in organic solvents.
<b>Specific Gravity:</b>	1.2
<b>Relative Vapour Density (air=1):</b>	Not available
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	>50
<b>Flammability Limits (%):</b>	1-8
<b>Autoignition Temperature (°C):</b>	450
<b>% Volatile by Weight:</b>	Not available
<b>Solubility in water (g/L):</b>	Insoluble
<b>Melting Point/Range (°C):</b>	Not applicable
<b>Boiling Point/Range (°C):</b>	110
<b>Decomposition Point (°C):</b>	Not available
<b>pH:</b>	Not applicable
<b>Viscosity:</b>	Not available
<b>Evaporation Rate:</b>	Not available

## 10. STABILITY AND REACTIVITY

<b>Chemical stability:</b>	Stable under normal conditions of use.
<b>Conditions to avoid:</b>	Avoid exposure to moisture.
<b>Incompatible materials:</b>	Incompatible with acids , alcohols , alkalis , amines and oxidising agents .
<b>Hazardous decomposition products:</b>	Hydrogen cyanide. Isocyanate vapours. Oxides of carbon. Oxides of nitrogen.
<b>Hazardous reactions:</b>	Reacts with moisture liberating carbon dioxide .

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	Swallowing may result in nausea, vomiting, and abdominal pain.
<b>Eye contact:</b>	May be an eye irritant.
<b>Skin contact:</b>	Contact with skin may result in irritation. May cause skin sensitisation in sensitive individuals. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
<b>Inhalation:</b>	Material is irritant to the mucous membranes of the respiratory tract (airways). A respiratory sensitiser. Can cause possible allergic reactions, producing asthma-like symptoms.

**Long Term Effects:**  
No information available for the product.

**Toxicological Data:** No LD50 data available for the product.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

Product Name: FLEXISTIK  
Substance No: 000000022733

Issued: 26/09/2011  
Version: 2

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

<b>Classification:</b>	This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.
<b>Hazard Category:</b>	Xn: Harmful
<b>Risk Phrase(s):</b>	R42: May cause sensitisation by inhalation.
<b>Safety Phrase(s):</b>	S23: Do not breathe vapour/mist/aerosol. S24/25: Avoid contact with skin and eyes. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
<b>Poisons Schedule:</b>	None allocated.

## 16. OTHER INFORMATION

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)  
Fax: 1300 555 305 (Australia wide)  
Phone: 0800 735 539 (New Zealand)  
Fax: 0800 804 583 (New Zealand)

### Reason(s) for Issue:

Revised Scanned MSDS  
Change in Formulation

# Safety Data Sheet



This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.